



e TRUCK MATE



Basic Parameter	
Drive type	4×2
Steering wheel position	RHD
Cabin	Single
The width of body (mm)	1520
Max Speed (Km/h)	90
Max climbing ability Degrees	25
Power Battery	
Battery type	Lithium Iron Phosphate
Battery Capacity (kwh)	38.64
Endurance mileage(Km)	280(NEDC)
Nominal Voltage (V)	309.12
Battery Structure	1 Case, 1 Parallel 96 Series
Battery Supplier	CATL
Charging type	CCS Type 2
Motor	
Motor Type	Permanent Magnet Synchronous Motor
Motor Model	FTBPO60A
Motor Power (Rated /Peak) (KW)	30/60
Motor Torque (Rated /Peak) (N.m)	100/220
Motor Rotate (Rated /Peak) (r/min)	2865/9000
Motor Supplier	Foton Motor
On-board Charger	
Charging Power (KW)	6.6
Charging Voltage (V)	250-450V
AC Charging Current (A)	32
Charging mode	DC/AC
Charging time	DC:1.5h AC:7h
Dimension	
Chassis dimensions (mm)	4670×1590×1860
Plate dimensions (mm)	4880×1680×1945
Cargo box dimensions (mm)	3050×1560×1570
FOH/ROH (mm)	1075/1205
Wheel base (mm)	2600
Wheel track (mm)	1320/1410
Weight	
GVW (Kg)	2540
Payload (Kg)	1380
Curb weigh-Chassis (Kg)	1170
Chassis	
Steering type	Electric Power Steering
Braking system	Disc / Drum
Front axle	1T
Rear axle/Ratio	2T/ Ratio: 10.5
Suspension	Independant Front/ Leaf springs rear
Tire	175R14
Others	
ABS+EBD	•
Electric door and window	•
Central lock	•
Front fog light	•
LED daytime running light	•
Air conditioning	•
Mp5	•
Air deflector	◦
Leather seats	◦